

SPECIFICATIONS

Round Post Key Lock Stainless Steel Removable Bollards (RP3503S, RP3503SL,
RP3504S, RP3504SL, RP3506S, RP3506SL)

Protected by U.S. Patent Numbers 7,472,891 and 7,722,285

PART 1 GENERAL

1.1 SECTION INCLUDES

1.1.1 Removable bollards and ground sleeves

1.2 PART SPECIFICATIONS

1.2.1 ASTM A312– bollard post

1.2.2 ASTM A513 Type 5 – bollard ground sleeve, filler piece

1.2.3 ASTM A276, A479, A580 – stainless steel lock rods

1.2.4 ASTM A554 - stainless steel lock rod channel

1.3 PERFORMANCE REQUIREMENTS

1.3.1 Bollard will remove completely from the ground sleeve and provide flush surface when bollard post is replaced with galvanized filler piece.

1.3.2 Unlock cam lock to allow the bollard to be removed. To replace the bollard, make sure the bollard is still unlocked, replace, and lock the cam lock to secure bollard in ground sleeve.

1.4 SUBMITTALS

1.4.1 Submittal document can be found at www.trafficguard.net under “document library” or enclosed with bollard purchase. Follow manufacturer’s specifications and installation instructions as required.

1.5 QUALITY

1.5.1 Bollard posts and ground sleeves must be supplied by TrafficGuard to provide consistent quality in appearance and performance.

1.6 DELIVERY, STORAGE AND HANDLING

1.6.1 Inspect materials upon receipt ensure that the correct materials have been received and that they are in good condition.

- 1.6.2 If not installing immediately, store units to avoid damage from other construction activities and elements.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- 2.1.1 TrafficGuard, Inc., P.O. Box 201, Geneva, IL 60134, Tel 877-727-7347, Fax 800-814-7194, Website: <http://www.trafficguard.net>
- 2.1.2 Different body styles for the Round Post Key Lock are available to fit strength and aesthetic requirements.
Architect should specify different body styles:
 - RP3503S - 3.5" OD, 36" height
 - RP3503SL- 3.5" OD, 36" height
 - RP3504S – 4.5" OD, 36" height
 - RP3504SL – 4.5" OD, 36" height
 - RP3506S – 6.625" OD, 36" height
 - RP3506SL – 6.625" OD, 36" height
- 2.1.3 All TrafficGuard Round Post Key Lock have a removable lid (by keyed allen wrench) to enable repair.

2.2 MATERIALS

- 2.2.1 Bollards supplied should be free from surface blemishes and defects where exposed to view in the finished installation.
- 2.2.2 Steel Tube: ASTM A312, ASTM A513, Type 5
- 2.2.3 Steel Lock Rods: ASTM A276, ASTM A479, ASTM A580
- 2.2.4 Steel tube $\frac{3}{4}$ " x $\frac{3}{4}$ " for Lock Rod to be ASTM A554

2.3 FABRICATION

- 2.3.1 After fabrication all units are prepared by removing scale and slag through the sand blasting process.

2.4 FINISHES

- 2.4.1 304 Stainless Steel, #4 Brushed Finish.

PART 3 EXECUTION

3.1 INSTALLATION

- 3.1.1 Comply with manufacturer provided instructions and drawings.

- 3.1.2 Ground sleeves should be installed with the top of the sleeve set flush with the finished surface.
- 3.1.3 Ensure that a minimum of a 3 inch gravel base is put down prior to installation to ensure drainage of the bollard, per installation details.
- 3.1.4 Bollard should not be inserted into the ground sleeve until it is leveled and fully cured. Attach bollard per manufacturer instructions. **DO NOT ATTEMPT TO INSTALL BOLLARD IN THE LOCKED POSITION.**
- 3.1.5 If touch up painting in the field, be careful not to paint moving parts which may restrict the bollard's proper function.

3.2 SITE STORAGE AND PROTECTION

- 3.2.1 Upon receipt of bollard unit(s) all materials should be thoroughly inspected to ensure that all parts are received in good condition.
- 3.2.2 Store units in a dry location away from possible damage until the time of installation.